


TRIDENT


FOAMATE™

FOAMATE Model ATP 1.0 CLASS A Foam Proportioner




Competitive Advantages

- ▶ All Brass Body and Construction
- ▶ Maximum Pressure 600 PSI
- ▶ Two Cleanable Strainers Included
- ▶ Panel or Bracket Mounting
- ▶ Simple Operation and Training
- ▶ GPM or LPM Calibrations



Simple Bracket Mount ▶

Panel Mount ▼



Performance Range


At 100 PSI [6.9 Bar]

- 400-GPM [1500-LPM] at 0.25%
- 200-GPM [750-LPM] at 0.50%
- 100-GPM [375-LPM] at 1.0%

Two Cleanable Wye Strainers Included:

- ▶ One for Foam
- ▶ One for Water

Valve may be added to water strainer cleanout for flushing.



FOAMATE™ 1.0 Product Features

- ▶ Wildland Slip-On Units
- ▶ Municipal Pumps
- ▶ Separate Foam-On Knob
- ▶ Flush in Foam-Off Position
- ▶ Factory Calibrated
- ▶ Low Cost Complete Assembly
- ▶ Certified to NFPA Standards



FOAMATE™ 1.0 Details

- ▶ Eductor Water Connection is 1/4" FNPT
- ▶ Eductor Foam Solution Connection is 3/8" FNPT
- ▶ Eductor Foam Concentrate Connection is 3/4" MGHT
- ▶ Driving Water Flow is 5-GPM at 100-PSI
- ▶ Wye Strainer Connection is 3/4" FNPT at Each End
- ▶ Wye Strainer Cleanout Thread is 1/2" FNPT

FOAMATE™ 1.0 Part Numbers are **GPM: 31.008.0** or **LPM: 31.008.1**


Optional Foam Pick-Up Tube is Part Number: **10.010.0**

TridentDirect.com


TRIDENT

FOAMATE™

FOAMATE Model ATP 2.1 CLASS B Foam Proportioner



Redesigned for Improved Panel Mounting
Available in GPM or LPM Models



FOAMATE™ 2.1 Product Features

- ▶ For Industrial or Municipal Pumpers
- ▶ Integrated Flow GPM/LPM Dial with 1%, 3% & 6% Scale
- ▶ Metering Valve is Panel Mountable
- ▶ All Brass Construction
- ▶ Factory Calibrated
- ▶ Certified to NFPA Standards

FOAMATE™ 2.1 Details

- ▶ Eductor Water Connection is 1.5" Victaulic
 - ▶ Eductor Foam Solution Connection is 2" Victaulic
 - ▶ Eductor Foam Concentrate Connection is 2" Victaulic
 - ▶ Driving Water Flow is 85-GPM at 125-PSI
 - ▶ Check Valve Connections are 2" FNPT
 - ▶ Ball Valve Connections are 2" FNPT
 - ▶ Metering Valve Connections are 2" Victaulic or 2" FNPT
- Refer to the list below to make your foam system selection.*

FOAMATE 2.1 ATP Part Numbers

Part #	2" Metering Valve	Dial Plate	Valves
31.014.2	Victaulic Ends	GPM	No
31.014.3	Victaulic Ends	[LPM]	No
31.014.4	Victaulic Ends	GPM	Yes
31.014.5	Victaulic Ends	[LPM]	Yes
31.014.12	FNPT Ends	GPM	No
31.014.13	FNPT Ends	[LPM]	No
31.014.14	FNPT Ends	GPM	Yes
31.014.15	FNPT Ends	[LPM]	Yes



Performance Range
At 125-250 PSI [8.5-17 Bar]

2000-GPM [8000-LPM] at 1%
2000-GPM [8000-LPM] at 3%
1000-GPM [4000-LPM] at 6%

Trident Emergency Products, LLC

2940 Turnpike Drive | Suite #9 | Hatboro, Pennsylvania 19040 USA
215-293-0700 Phone
215-293-0701 Fax
sales@tridentdirect.com Email

TridentDirect.com

Revised • 12/28/2016



<https://www.facebook.com/tridentemergency>



World Class
Fire Apparatus
Plumbing and
Hardware Products

FOAMATE™ is a trademark of
Trident Emergency Products, LLC